

Certificate of Compliance

Certificate Number:

UL-US-L76491-2116-
12404991-6

Report Reference:

E76491-19940421

Issue Date:

2025-04-01

Issued to:

MERSEN FRANCE SB S A S
15 RUE DE VAUCANSON ST BONNET DE MURE 69720
France

This certificate confirms that representative samples of:

JFHR2 - Special-purpose Fuses - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 248-1, 4th Ed., Issue Date: 2022-10-24, UL 248-13, Edition 3,
Issue Date 2022-03-31

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L76491-2116-12404991-6
Report reference E76491-19940421
Date 2025-04-01

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Fuses - Special Purpose

Model(s): 10URD71, 10URD72, 10URD72TTF0900, 10URD73, 11URD272 or 2x72, 11URD273 or 2x73, 11URD70TTF0400, 11URD71, 11URD72, 11URD73, 12,5URD272 or 2x72, 12,5URD273 or 2x73, 12,5URD70, 12,5URD71, 12,5URD72, 12,5URD73, 12URD70, 12URD73, 6,6URD73, 6URD73, 8,5URD273 or 2x73, 8,5URD73, 8URD71TTF 0900, 9,5URD273 or 2x73, 9,5URD73, 9URD273 or 2x73, 9URD73, A065URD73, A070URD73, A090URD73, A100URD73, A110URD72, A110URD73, A120URD70, A120URD71, A120URD72, A120URD73, A130URD70, A130URD71, A130URD72, A130URD73, PC70UD11C

Component special purpose fuses

Model(s): 10URD71TTF0700, 8URD71TTF0900

Component special purpose fuses, semiconductor protection fuses

Model(s): 10 URD 72 TTF 0900, 11 URD 70 TTF 0400

Special purpose semi-conductor protection fuses, with or without indicators

Model(s): A065UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A070UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A090UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A100UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A110UR, followed by C, D or E, followed by body size 72, followed by suffix letters, A110UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A120UR, followed by C, D or E, followed by body size 70, followed by suffix letters, A120UR, followed by C, D or E, followed by body size 71, followed by suffix letters, A120UR, followed by C, D or E, followed by body size 72, followed by suffix letters, A120UR, followed by C, D or E, followed by body size 73, followed by suffix letters, PC272UD11C, PC272UD13C, PC273UD11C, PC273UD13C, PC273UD85V, PC273UD90V, PC273UD95V, PC70UD12C, PC70UD13C, PC71UD10C, PC71UD11C, PC71UD13C, PC72UD10C, PC72UD11C, PC72UD13C, PC73UD10C, PC73UD11C, PC73UD12C, PC73UD13C, PC73UD60V, PC73UD66, PC73UD85V, PC73UD90V, PC73UD95V

Model(s): A130UR, followed by C, D or E, followed by body size 72 followed by suffix letters, followed by current range 280 thru 630 or 630 thru 1250, followed by body size suffix 2, may be followed by additional suffixes

Model(s): A130UR, followed by C, D or E, followed by body size 70 followed by suffix letters, followed by current range 63 thru 315, may be followed by additional suffixes

Model(s): A130UR, followed by C, D or E, followed by body size 71 followed by suffix letters, followed by current range 160 thru 450, may be followed by additional suffixes

Model(s): A130UR, followed by C, D or E, followed by body size 73 followed by suffix letters, followed by current range 315 thru 900 or 1250 thru 1800, followed by body size suffix 2, may be followed by additional suffixes



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-2418254-1

Report Reference:

E76491-19940421

Issue Date:

2025-04-01

Issued to:

MERSEN FRANCE SB S A S
15 RUE DE VAUCANSON ST BONNET DE MURE 69720
France

This certificate confirms that representative samples of:
JFHR8 - Special-purpose Fuses Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 No. 248.1:22, 4th Ed., Issue Date: 2022-10-24, CSA C22.2 No. 248.13:22, 3rd Ed., Issue Date: 2022-03-31

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2418254-1
Report reference E76491-19940421
Date 2025-04-01

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Fuses - Special Purpose

Model(s): 10URD71, 10URD72, 10URD73, 11URD272 or 2x72, 11URD273 or 2x73, 11URD70TTF0400, 11URD71, 11URD72, 11URD73, 12,5URD272 or 2x72, 12,5URD273 or 2x73, 12,5URD70, 12,5URD71, 12,5URD72, 12,5URD73, 12URD70, 12URD73, 6,6URD73, 6URD73, 8,5URD273 or 2x73, 8,5URD73, 9,5URD273 or 2x73, 9,5URD73, 9URD273 or 2x73, 9URD73, A110URD72, A110URD73, A120URD70, A120URD71, A120URD72, A130URD70, A130URD71, A130URD72, A130URD73, PC70UD11C

Component special purpose fuses

Model(s): 10URD71TTF0700, 8URD71TTF0900

Component special purpose fuses, semiconductor protection fuses

Model(s): 10 URD 72 TTF 0900, 11 URD 70 TTF 0400

Special purpose semi-conductor protection fuses, with or without indicators

Model(s): A065UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A070UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A090UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A100UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A110UR, followed by C, D or E, followed by body size 73, followed by suffix letters, A120UR, followed by C, D or E, followed by body size 70, followed by suffix letters, A120UR, followed by C, D or E, followed by body size 71, followed by suffix letters, A120UR, followed by C, D or E, followed by body size 72, followed by suffix letters, A120UR, followed by C, D or E, followed by body size 73, followed by suffix letters, PC70UD13C, PC72UD13C, PC73UD13C

Model(s): A130UR, followed by C, D or E, followed by body size 72 followed by suffix letters, followed by current range 280 thru 630 or 630 thru 1250, followed by body size suffix 2, may be followed by additional suffixes

Model(s): A130UR, followed by C, D or E, followed by body size 70 followed by suffix letters, followed by current range 63 thru 315, may be followed by additional suffixes

Model(s): A130UR, followed by C, D or E, followed by body size 71 followed by suffix letters, followed by current range 160 thru 450, may be followed by additional suffixes

Model(s): A130UR, followed by C, D or E, followed by body size 73 followed by suffix letters, followed by current range 315 thru 900 or 1250 thru 1800, followed by body size suffix 2, may be followed by additional suffixes



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.