

We MERSEN USA EP Corp.
374 Merrimac Street Newburyport, MA 01950 USA

Certify that products with the registered trade mark Mersen Ferraz Shawmut

Product type Medium Voltage IEEE Fuses
Potential Transformer Protection Fuses

Model Series Line .625kV to 15.5 kV PT Fuses

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:

RoHS directive N° 2011/65/UE

RoHS directive N° 2015/863

https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided below is based on data obtained through ongoing due diligence with our suppliers. In some cases, the information may not yet represent full coverage of our supply chain. Mersen reserves the right to update or amend this declaration as additional data becomes available, or verification processes are completed.

This declaration is not an EU or UKCA declaration of conformity, Mersen USA EP Corp. is providing RoHS conformity to all product ranges even if they are out of the scope of the directive with the same level of compliance on substances restrictions and corresponding exemptions.

Date / Location : 10.02.2026 / Newburyport

Name : Tim KAPPEN

Position / Signature :

Sr. Manager Quality
For the president and by delegation

Catalog number list

Item number	ROHS exemption
A240T5E	
A240T1E	
A240T2E	
A240T1/2E	
A480T5E	
A480T3/4E	
A480T1E	
A480T2E	
A480T3E	
A480T4E	
A480T1/2E	
A500T5E-1	
A500T4E-1	
A500T2E-1	
A500T1/2E-1	
A500T1/4E-1	
A500T1E-1	
A500T3E-1	
A720T3/4E-1	
A720T3E-1	
A720T2E-1	
A720T1E-1	
A720T1/2E-1	
9F60AAA003	
9F60AAA005	
9F60AAA007	
9F60AAA010	
9F60AAB001	
9F60AAB002	
9F60BBB001	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBB002	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBB003	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBD001	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBD002	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBD003	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBD905	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBD001-S	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBD002-S	6(c) - Copper alloy containing up to 4% lead by weight
9F60BBN002	

COMP-015091

9F60BBN003	
9F60BBN001	
9F60BBN905	
9F60BDB001	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDB002	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDB003	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDD001	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDD002	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDD003	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDD905	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDE001	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDE002	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDE003	6(c) - Copper alloy containing up to 4% lead by weight
9F60BDE905	6(c) - Copper alloy containing up to 4% lead by weight
9F60BHH001	6(c) - Copper alloy containing up to 4% lead by weight
9F60BHH002	6(c) - Copper alloy containing up to 4% lead by weight
9F60BHH003	6(c) - Copper alloy containing up to 4% lead by weight
9F60BHH905	6(c) - Copper alloy containing up to 4% lead by weight