RoHS COMPLIANCE STATEMENT

We MERSEN FRANCE SB
15, Rue Jacques de Vaucanson 69720 SAINT BONNET DE MURE FRANCE

Certify that products with the registered trade mark Mersen

Product type EV and Battery Protection Fuses
Battery Energy Systems

Model Series Line ABAT15C 1500VDC max

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:
RoHS directive N° 2011/65/UE
RoHS directive N° 2015/863
https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided is based upon data obtained from ongoing due diligence concerning goods and materials provided by our suppliers. Mersen reserves the right to update and modify this communication, as it believes necessary or appropriate.

Date / Location : 28.04.2026 / Saint Bonnet de Mure

Name : Pierre LAVAUD

Position / Signature : Head of R&D department
For the president and by delegation
Pierre Lavaud

COMP-015381

Catalog number list

Catalog number	Item number	ROHS exemption
ABAT15C1000-AIB	H1200492	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C1250-AIA	J1200493	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C500-AIA	B1200486	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C550-AIA	C1200487	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C630-AIA	D1200488	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C700-AIA	E1200489	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C800-AIA	F1200490	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C900-AIA	G1200491	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C550-AJA	Q1201189	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C1000-LIA	P1215724	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C1100-LIA	W1213223	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C500-LIA	E1215715	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C550-LIA	G1215717	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only

		and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C630-LIA	H1215718	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C700-LIA	M1215722	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C800-LIA	N1215723	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
ABAT15C900-LIA	P1209629	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)