RoHS COMPLIANCE STATEMENT

We MERSEN USA EP Corp.
374 Merrimac Street Newburyport, MA 01950 USA

Certify that products with the registered trade mark Mersen Ferraz Shawmut

Product type High-Speed and Semiconductor protection fuses
Round Body High-Speed Fuse-Links AC Protection

Model Series Line Amp-Trap® A15QS 150VAC 150VDC

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:
RoHS directive N° 2011/65/UE
RoHS directive N° 2015/863
https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided below is based on data obtained through ongoing due diligence with our suppliers. In some cases, the information may not yet represent full coverage of our supply chain. Mersen reserves the right to update or amend this declaration as additional data becomes available, or verification processes are completed.

This declaration is not an EU or UKCA declaration of conformity, Mersen USA EP Corp. is providing RoHS conformity to all product ranges even if they are out of the scope of the directive with the same level of compliance on substances restrictions and corresponding exemptions.

Date / Location : 18.05.2026 / Newburyport

Name : Tim KAPPEN

Position / Signature : Sr. Manager Quality
For the president and by delegation Tim Kappen

COMP-016680

Catalog number list

Item number	ROHS exemption
A15QS1000-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS500-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS600-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS800-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS700-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS900-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS550-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS1000-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS450-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS500-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS600-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS700-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS800-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS900-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS550-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS1000-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS600-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS500-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS700-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS800-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS900-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS550-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS1000-128	
A15QS1200-128	
A15QS1500-128	
A15QS2000-128	
A15QS750-128	
A15QS800-128	

COMP-016680

A15QS1600-128	
A15QS1800-128	
A15QS1000-128IL	
A15QS1200-128IL	
A15QS1500-128IL	
A15QS2000-128IL	
A15QS750-128IL	
A15QS800-128IL	
A15QS1600-128IL	
A15QS1800-128IL	
A15QS1-2	6(c) - Copper alloy containing up to 4% lead by weight
A15QS2-2	6(c) - Copper alloy containing up to 4% lead by weight
A15QS3-2	6(c) - Copper alloy containing up to 4% lead by weight
A15QS4-2	6(c) - Copper alloy containing up to 4% lead by weight
A15QS5-2	6(c) - Copper alloy containing up to 4% lead by weight
A15QS6-2	6(c) - Copper alloy containing up to 4% lead by weight
A15QS10-2	
A15QS20-2	
A15QS25-2	
A15QS30-2	
A15QS2500-128	6(c) - Copper alloy containing up to 4% lead by weight
A15QS3000-128	6(c) - Copper alloy containing up to 4% lead by weight
A15QS2500-128IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS3000-128IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS3500-128	6(c) - Copper alloy containing up to 4% lead by weight
A15QS4000-128	6(c) - Copper alloy containing up to 4% lead by weight
A15QS3500-128IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS4000-128IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS150-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS200-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS300-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS400-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS20-4IL	6(c) - Copper alloy containing up to 4% lead by weight

A15QS30-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS40-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS50-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS60-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS70-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS80-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS90-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS100-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS130-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS225-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS250-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS350-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS275-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS25-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS35-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS45-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS125-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS175-4IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS100-4	
A15QS130-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS150-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS200-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS250-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS300-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS350-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS400-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS450-4	6(c) - Copper alloy containing up to 4% lead by weight

A15QS50-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS70-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS80-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS90-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS20-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS30-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS40-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS60-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS225-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS275-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS25-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS35-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS45-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS125-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS175-4	6(c) - Copper alloy containing up to 4% lead by weight
A15QS100-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS130-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS150-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS20-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS225-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS250-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS300-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS350-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS40-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS400-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS50-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS70-4TI	6(c) - Copper alloy containing up to 4% lead by weight

COMP-016680

A15QS80-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS30-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS60-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS90-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS200-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS450-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS275-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS25-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS35-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS45-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS125-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS175-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A15QS5000-128	6(c) - Copper alloy containing up to 4% lead by weight
A15QS6000-128	6(c) - Copper alloy containing up to 4% lead by weight
A15QS4500-128	6(c) - Copper alloy containing up to 4% lead by weight
A15QS5000-128IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS6000-128IL	6(c) - Copper alloy containing up to 4% lead by weight
A15QS4500-128IL	6(c) - Copper alloy containing up to 4% lead by weight